

BioClean Clearview™

STERILE LOOPED AND TIE-ON VISOR FACEMASKS



VFM
Re-order Code

BioClean Clearview™ sterile cleanroom visor facemasks will not compromise your sterile environment and are easier to manage and control than sanitising disposable goggles, which could lead to product contamination.

Our, 'Splash Protection', visor facemasks are 3-ply with a 3M Anti-fog visor which is optically clear and distortion free. User comfort is assured with a hydrophilic inner layer to absorb moisture and safety is enhanced by the hydrophobic outer layer that is liquid repellent.

Lint-free with very low particle release, our visor facemasks are suitable for use in ISO Class 4 environments and are 210mm width for maximum coverage.



GB04/61092



ISO 9001
REGISTERED FIRM

NITRITEX LTD.

T: +44 (0) 1638 663338

E: info@nitritex.com

NITRITEX ASIA PTE LTD.

T: +65 6536 9123

E: nitritex@pacific.net.sg

NITRITEX PUERTO RICO Inc.

T: +1 787 309 3979

E: info@nitritex.com.pr

NITRITEX CANADA LTD.

T: +1 (905) 946 9539

E: info@nitritexcanada.com


NITRITEX MALAYSIA Sdn. Bhd.

T: +(603) 3122 2614

E: info@nitritex.com.my

Nitritex
www.nitritex.com

STERILE LOOPED AND TIE-ON VISOR FACEMASKS

Colour:	White.		
Style/Type:	Earloop.	Each mask is supplied with a plastic connector clip.	
	Tie-on.		
Size:	Mask size:	210mm Length; 90mm width	
	Visor:	3M anti-fog visor - 0.18 mm thickness (7 ml).	
Construction:	3-ply - ultrasonic sealing.		
	Outer facing:	Hydrophobic Polyester (Non Woven).	
	Filter layer:	Meltblown Polyester.	
	Inner facing:	Hydrophilic Polypropylene/PE (Non Woven).	
	Earloops:	Polyurethane.	
Protein Level:	Contains no latex proteins.		
Sterilisation Method:	Gamma Irradiation.		
Physical Properties:	Particle filtration efficiency (PFE):	>96%	
	Bacterial filtration efficiency (BFE):	>94%	
	Pressure Drop (Delta P):	3.2	
Packing:	Bagged.		
Particle Shedding Analysis:	Average Particle Count = 19 / minute (Particle size: 0.2 - 5.0 microns).		
Test method:	ASTM F51-68 (1989).		
Quality Systems:	Produced in a facility registered to ISO 9001:2000 and ISO 13485:2003.		
Sampling & Inspection:	In accordance with ISO 2859 standard procedures.		
Storage Instructions:	Store in a dry, cool place (<40°C) away from direct sunlight and fluorescent light.		
Shelf Life:	Five (5) years from date of manufacture.		
Bar Codes:	This appears on the outer carton to allow automatic data entry into Stock Control Systems.		
Lot Number:	This appears on all the bags and the outer carton to provide traceability.		
Packaging:	Earloop:	One mask & plastic clip per sealed easy-tear polybag; 25 polybags per sealed outer bag; Four outer bags per carton (100 pieces).	
	Tie-on:	One piece per sealed easy-tear polybag; 25 polybags per sealed outer bag; Four outer bags per carton (100 pieces).	
Compatibility:	ISO Class 4.		
Product Codes and Sizes:	Earloop:	VFM210-L	Universal.
	Tie-on:	VFM210-T	Universal.